



DATASHEET



SHE2BP

230V IP65 18W LED Eyelid Bulkhead CCT with Daylight Sensor Black

www.mlaccessories.co.uk



MLA PART CODE	SHE2BP
DESCRIPTION	230V IP65 18W LED Eyelid Bulkhead CCT with Daylight Sensor Black
NET WEIGHT (KG)	2.475
FINISH	Black
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 360 Projection - 94
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	I
IP RATING	IP65
IK RATING	IK10
WATTAGE (W)	18
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1020/1080/1090
LUMENS LIGHT SOURCE ONLY (LM)	3000
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	133
CIRCUIT WATTAGE (W)	22.6
CCT	3000/4000/6000K
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.09
DISPLACEMENT FACTOR	>0.7
SVM	0.005
PST-LM	0.12
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes

DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 21W OUTPUT VOLTAGE - 28-42V OUTPUT CURRENT - 500mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 86 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
SENSOR TYPE	Photocell
SENSOR LUX SETTINGS	5-25lx - 200-400lx
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270800258

Date Created: 21/01/2026 15:18

